

# Industrial Rubber Hose and Tubing

## Hoses Engineered for the Steel Industry:

### Furnace FG-Plus(FG-P)

One ply fiberglass cover offers temperature resistance to 1000°F–100psi maximum rated WP will meet or exceed most operating systems.

ID (in)	# PLY	OD (in)	LBS/FT	WP (psi)
1/2	2	0.98	0.25	100
3/4	2	1.23	0.34	100
1*	2	1.48	0.43	100
1-1/4*	2	1.81	0.64	100
1-1/2*	2	2.12	0.85	100
2*	4	2.68	1.20	100
2-1/2	4	3.18	1.46	100
3	4	3.74	1.92	100
4	4	4.74	2.49	100

### Furnace FG-Max(FG-M)

Two ply fiberglass cover offers temperature resistance to 1000 F longer than any one ply manufactured hose–150psi maximum rated WP will meet or exceed most operating systems.

ID (in)	# PLY	OD (in)	LBS/FT	WP (psi)
1/2	2	1.20	0.40	150
3/4	2	1.45	0.52	150
1	2	1.70	0.64	150
1-1/4	2	1.95	0.77	150
1-1/2	2	2.25	0.97	150
2	4	2.90	1.57	150
2-1/2	4	3.40	1.90	150
3	4	3.96	2.43	150
4	4	4.96	3.14	150

\*Other heat resistant fabrics available upon request.

